

PGK10

DESCRIPTION

- Industrial protective glove.
- Natural rubber latex supported glove.
- 5 sizes available : 7, 8, 9, 10 and 11.
- Trade unit 12 pairs, 72 pairs in a transit case.

CHARACTERISTICS

- Mediumweight 10 gauge 100% Kevlar liner.
- Seamless construction eliminates irritation from seams.
- Natural rubber latex palm fit coating, with wrinkle finish.
- Fully coated thumb to protect one of the most vulnerable parts of the hand.
- Latex knit wrist to ensure snug fit.

PERFORMANCES

- Highest levels of cut, tear and puncture resistance.
- Excellent grip properties in both wet and dry environments.
- Open back reduces perspiration build up.
- High flexibility and comfort.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical hazards) by the notified laboratory INSPEC.

APPLICATIONS

- Ideal for abrasive and cutting applications.
- Applications : construction, refuse collection, general handling work, automotive industry and glazing.

LIMITATIONS

- Do not use for handling liquids or pointed objects.
- Do not use with a rotating machine in which glove may get caught.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN 420

EN 420

5 Dexterity



2544

EN 388

EN 388
Mechanical hazards

EN 388

2 Abrasion

5 Cut

4 Tear

4 Puncture

			Order codes		
Sizes	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
PGK10	M10153	M10154	M10155	M10156	M9999117

