

# Green Nitrile G25G

## DESCRIPTION

- Industrial protective glove.
- Green synthetic unsupported glove.
- 5 sizes available: 6.5, 7.5, 8.5, 9.5 and 10.5.
- Trade unit 12 pairs, 144 pairs in a transit case.

## CHARACTERISTICS

- Flock lined 100% cotton nitrile formula glove.
- Open cuff allows ventilation to keep hand cool.
- Raised diamond pattern.
- Length :330 mm approx.
- Double wall thickness : 0,84 mm approx.

## PERFORMANCES

- Excellent resistance to many solvents and oil based chemicals.
- Very good abrasion resistance.
- Flexible and comfortable for an excellent dexterity.
- Superior raised grip pattern for safety handlings.
- In compliance with the standards EN420 (General requirements), EN388 (Mechanical Hazards) and EN374 (Chemical and Micro-organisms Hazards) by the notified laboratory BSI.
- Manufactured under EC quality assurance system carried out by the BSI.

## APPLICATIONS

- CE Complex Design.
- Ideal for use in maintenance, automotive and printing industries, food industry.



*This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests, and manufactured under a CE quality assurance system carried out by a notified body.*

**CE 0086**



EN 420

EN 420

**5** Dexterity

EN 388

**4** Abrasion

**1** Cut

**0** Tear

**1** Puncture

EN 374

**3** A - Methanol

**6** J - N-heptane

**6** K - Caustic soda solution  
40 %

**3** L - Sulfuric acid 96 %



**4101**

EN 388

Mechanical hazards



**AJKL**

EN 374

Chemical hazards



EN 374

Micro-organism hazards



### Order codes

Sizes	6.5 (S)	7.5 (M)	8.5 (L)	9.5 (XL)	10.5 (XXL)
Green Nitrile G25G	03271	03272	03273	03274	05747