Flexiproof

DESCRIPTION

- Industrial protective glove.
- Nitrile supported glove on a textile liner.
- 3 different lengths available:
- - 270mm (Flexiproof 27)
- - 350mm (Flexiproof 35)
- - 400mm (Flexiproof 40).
- 4 sizes available: 8, 9, 10 and 11.
- Trade unit: 10 pairs, 120, 100 and 80 pairs respectively for 270, 350 and 400mm in a transit case.

CHARACTERISTICS

- Fine gauge 100% cotton knitted liner.
- Integral nitrile coating, smooth finish.

PERFORMANCES

- Good dexterity and flexibility.
- Improved resistance to abrasion.
- Great comfort in intensive wear.
- In compliance with the standards EN420 (Mechanical Hazards), EN388 (Mechanical hazards), EN407 (Heat and/or fire) and EN374 (Chemical and Micro-organisms Hazards)by the notified laboratory Institut Français Textile Habillement.
- Manufactured under EC quality assurance system carried out by the BSI body.

APPLICATIONS

- Ideal for intensive tasks, handling of abrasive and sharp components, immersion in very aggressive chemicals, including solvents.

This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests, and manufactured under a CE quality assurance system carried out by a notified body.

CE 0086

EN 420

EN 420
5 Dexterity

4122

EN 388
Mechanical hazards

EN 388
4 Abrasion
1 Cut
2 Tear
2 Puncture

X1XXXX

EN 407
Heat and fire

EN 407
X Burning behaviour
1 Contact heat
X Convective heat
X Radiant heat
X Small drops molten metal
X Large drops molten metal

AJK

EN 374
Chemical hazards

EN 374
3 A - Methanol
6 J - N-heptane
6 K - Caustic soda solution 40 %

EN 374
Micro-organism hazards

Order codes

Sizes	8 (M)	9 (L)	10 (XL)	11 (XXL)
Flexiproof 27	1750E12000	1750E13000	1750E14000	1750E10000
Flexiproof 35	1770E12000	1770E13000	1770E14000	1770E10000
Flexiproof 40	1790E12000	1790E13000	1790E14000	1790E10000

www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com • www.comasec.com

N° CMS/TDS/FlexiproofEN/FT/11 - 07/09